MODELS KS 2004, KS 2006, KS 2008, KS 2010

SUBMITTAL DATA INFORMATION

Engineering Specifications

Construction. The one piece chassis with removable grille is manufactured from high grade zinc coated steel. The grille and exposed parts of the chassis are painted with a copper/brown baked enamel finish.

Heat Exchanger. A highly efficient, headered coil, made of copper tubes expanded into smooth aluminum plate fins (10 FPI), tested at 300 PSI, and sealed for quality. The heat exchanger is positioned in the kickspace for maximum heat transfer over the coil.

Fan and Motor Assembly. High spec tangential SEL fan and motor assembly consists of high static fan wheel and scroll, detachable motor, replaceable "easy glide" sleeve bearings, and the fan and motor cut out are protected to UL/CSA specifications. This fan and motor assembly is designed to enhance the "coanda" effect, and to run whisper quiet without vibration.


Controls. The KS units have integral two speed, max.-off-min., fan switches (optional wall mounted fan speed controller is available). The LTC — low limit aquastat is also a high spec item with a close tolerance designed to close on a rise to 130°F+/-3°F and open at 110°F+/-3°F. For low temperature systems you will have to change out the aquastat located in the main electrical box easily removed from its hold on clip.

Water Connections. Supply and return connections are ¹/₂" sweat connections located to the right of the unit as you face the grille. A water vent with wide convenient screwdriver slot is accessible through the grille.

Electrical Connections. 120/60/1 power supply is required. All that's required is to knock out the junction box hole you want to use and wire to the L1 and L2 leads. There is a convenient one screw access plate on the top of the unit to get at the ground.

Quiet Comfort! Performance and Style!

| Model # | A | В | C | D | Wt.(lbs.) | |
|---------|----------|----------|--------|---------|-----------|--|
| KS 2004 | 10%" | 13%" | 13%" | 3½" | 9 | |
| KS 2006 | 10%" | 131/8" | 20" | 313/16" | 10 | |
| KS 2008 | 10%" | 131/8" | 20" | 313/16" | 10 | |
| KS 2010 | 1413/32" | 1723/32" | 235/8" | 4" | 14 | |



| Fan Convecto | r/Baseboard | d Comparison |
|-------------------------------|----------------------------|--------------------------------------|
| At 200°F EWT; 20°TD Model# | At 650 BTU/FT Baseboard | Low Pressure Steam C.I. Radiators |
| KS 2004 | 6.97 linear ft. | 18.9 square ft. |
| KS 2006 | 11.6 linear ft. | 31.4 square ft. |
| KS 2008 | 14.5 linear ft. | 39.3 square ft. |
| KS 2010 | 17.8 linear ft. | 48.0 square ft. |

| C | apacity | for the | Quiet-0 | ne 2000 | Kickspa | ace Hea | ters - B1 | TU/HR @ | 9 65°F E | ntering | Air |
|------------|------------------------|---------------------------|---|---------|---------|---------|-----------|---------|----------|---------|-------|
| Unit | Flow Rate G.P.M. | Pressure Drop (ft.) | Entering Water Temperature (Deg. F.) - BTU/hrs. | | | | | | | | |
| | | | 130 | 140 | 150 | 160 | 170 | 180 | 190 | 200 | 210 |
| KS 2004 | 1 | 0.06 | 2095 | 2410 | 2700 | 3000 | 3350 | 3650 | 3860 | 4000 | 4105 |
| | 3 | 0.422 | 2240 | 2650 | 3000 | 3350 | 3765 | 4120 | 4350 | 4530 | 4635 |
| | 5 | 1.026 | 2350 | 2755 | 3140 | 3530 | 3940 | 4330 | 4590 | 4810 | 4935 |
| KS 2006 | 1 | 0.12 | 3410 | 4050 | 4655 | 5265 | 5860 | 6330 | 6700 | 7110 | 7270 |
| | 3 | 1.19 | 3735 | 4395 | 5060 | 5735 | 6330 | 6825 | 7120 | 7530 | 7790 |
| | 5 | 2.6 | 3860 | 4540 | 5225 | 5910 | 6560 | 7030 | 7415 | 7800 | 8010 |
| KS 2008 | 1 | 0.12 | 4300 | 5000 | 5765 | 6500 | 7370 | 7960 | 8400 | 8735 | 8920 |
| | 3 | 1.19 | 4580 | 5380 | 6195 | 7050 | 7930 | 8610 | 9010 | 9445 | 9740 |
| | 5 | 2.6 | 4760 | 5625 | 6450 | 7290 | 8200 | 8925 | 9360 | 9785 | 10020 |
| KS 2010 | 1 | 0.41 | 5530 | 6350 | 7150 | 7975 | 8780 | 9465 | 9975 | 10330 | 10520 |
| | 3 | 2.78 | 5880 | 6710 | 7740 | 8710 | 9625 | 10540 | 11060 | 11530 | 11740 |
| | 5 | 3.92 | 6070 | 7030 | 8000 | 9030 | 10025 | 10920 | 11525 | 11995 | 12180 |

- All capacities are rated by RTS with the kickspace installed under a cabinet. That is, they are not rated in free air.
- For low speed ratings use: .85 for the KS2004, .75 for the KS2006, .70 for the KS2008, and .65 for the KS2010.
- Heat throw: KS2004 = 10 ft. @ 50 CFM; KS2006 = 10 ft. @ 75 CFM; KS2008 = 10 ft. @ 90 CFM; KS2010 = 10 ft. @ 125 CFM.

As part of our continuous product improvement, Smith's Environmental Products reserves the right to alter specifications without notice.

